



JETTY DESCRIPTIONS
--------------------

	Dock 1		Dock 2		Dock 3		Comments
Docking basin: tidal range max. 60 cm	Canal Bossière		Canal Bossière		Henri Deschênes Basin		Constant-level basin
Arm	DIESEL	FUEL OIL	DIESEL	FUEL OIL	DIESEL	FUEL OIL	
Maximum output rate (m <sup>3</sup> /h)	550	550	1,200	1,100	1,500	1,500	
Average output rate (m <sup>3</sup> /h)	550	550	1,000	500	1,000	1,000	
Maximum pressure (bar)	7	7	7	7	8	8	
Maximum temperature (°C)	55	80	55	90	55	90	
Min./max. distance from the flange to the rail (m)	1	3	1	4	2	4.6	
Maximum lateral motion (m)	3	3	3	3	3	3	
Line diameter (in inches)	12	12	12	12	14	14	
Arm diameter (in inches)	8	8	10	10	12	12	
Connection diameter (in inches)	8	8	10	10	12	12	
Equipped with a vacuum breaker	No	No	No	No	No	No	
Type of connection	Screw couplings		Screw couplings		Screw couplings		
Load carrying capacity (Tonnes)	5,000		33,000		105,000		
Draft (m)	6.5		10		13.3		The exact draft must be requested from GPMH (Le Havre Harbor)
Manifold <-> water line distance (m)	9		11.3		16.5		
Jetty length (m)	39		40		56		
Number of dolphins	4		5		4		Dolphins are equipped with mooring bollards
Length between internal dolphin axes (m)	24		27		50		
Length between external dolphin axes (m)	95		57		76		
Number of moorings ashore	3 (40 T) and 1 (25 T)		5 (40 T) and 3 (60 T)		6 (100 T)		
Maximum approach speed	0.25 m/s		0.16 m/s		0.2 m/s		
Maximum ship length (m)	150		185		280		
Jetty <-> dolphin distance (m)	2.1		2.6		2.1		